

TruTemp™ BatchOven



Standard Features:

- Nema 12 Rated Control Panel
- Aluminized Steel Construction
- Single Button E-stop on Control Panel
- Heating Safety Equipment
- Oven Temperature Control
- Factory-Testing

System Options:

- Powered Exhaust
- Shutdown Timer
- Disconnect
- Vertical Lift Door
- Composite Option (Vacuum Ports and associated equipment)
- Trolley Rail Cutouts
- Walk-Thru Design
- Floor Design - Plate, Insulated, Cart
- Powder Paint Setting and Curing
- Spare Parts Available
- Optional Voltages



TruTemp™ Batch Ovens offers industry leading heat processing technology at an affordable price point. Perfect for smaller applications and value driven projects.

Batch Ovens process products one at a time or in a single group.

TruTemp™ Batch Oven configuration styles include cart, walk-in, and pass-thru and are engineered to accommodate various sized products. Batch ovens can be used for a wide variety of heat processes including drying, curing, aging, stress relieving, bonding, tempering, preheating, and forming.

Our TruTemp™ Batch Oven line is offered in standard chamber sizes of 6', 8' & 10', and ITS can also design a custom oven for specific applications.

TruTemp™ BatchOven



MODEL #	CHAMBER WIDTH (in)	CHAMBER HEIGHT (in)	CHAMBER LENGTH (in)	OVEN WIDTH	OVEN HEIGHT	OVEN LENGTH	CFM REQ'D	VOLTAGE RANGE	ELECTRIC (kW)	GAS (BTU)								
TTO.060608D 6' X 6' X 8'	72	72	96	100	84	108	6,000	208/3/60 THROUGH 480/3/60	96	.5 MIL								
TTO.060608S 6' X 6' X 8'																		
TTO.060810D 6' X 8' X 10'											96	120	100	108	132	10,000		
TTO.060810S 6' X 8' X 10'																		
TTO.060812D 6' X 8' X 12'											96	144	100	108	156	12,000	144	1.0 MIL
TTO.060812S 6' X 8' X 12'																		
TTO.080808D 8' X 8' X 8'	96	96	96	124	108	108	9,000		144	1.0 MIL								
TTO.080808S 8' X 8' X 8'																		
TTO.080812D 8' X 8' X 12'											96	144	124	108	156	14,000	180	1.0 MIL
TTO.080812S 8' X 8' X 12'																		
TTO.080820D 8' X 8' X 20'											96	240	124	108	252	22,200	216	1.0 MIL
TTO.080820S 8' X 8' X 20'																		
TTO.100816D 10' X 8' X 16'	120	96	192	148	108	204	22,200	216	1.0 MIL									
TTO.100816S 10' X 8' X 16'																		
TTO.100820D 10' X 8' X 20'	120	96	240	148	108	252	27,700	216	1.0 MIL									
TTO.100820S 10' X 8' X 20'																		

Benefits of the TruTemp™ Batch Oven design are:

- 100% electric or gas fired heating
- Combination or horizontal air flow
- Variable air flow speeds for powder coat paint
- Plate, insulated or cart design floors